ift-Nachweis

Classification Report

20-001378-PR01 (NW-A01-02-en-01)

mensions (W x H) 1600 mm x 2200 mm

of the test and is tested separately.

Shipping name: EUROPA ESS 34 DOUBLE SLIDING

Manufacturer Europa Profil Aluminio S.A., - Innofita Viotas; Material Aluminium system with thermal break; Type of opening Sliding; Opening direction Sash right before sash left; Overall di-

Test sequence. Increased operating forces. The vapour pressure equalisation of the glazing rebate has to be ensured. Material compatibility must be taken into account. Material durability must be taken into account. Construction

with visible internal drainage. The strength, durability and

material compatibility of the adhesive system was not part

Europa Profil Aluminio S.A.

56th Klm National Highway

Athens - Lamia

Greece

32011 Innofita Viotas

Double sash sliding door System: EUROPA ESS 34



Representation



Instructions for use

The Evidence ("Nachweis") can be used for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The results obtained apply to the direct field of application determined in Annex E of EN 14351-1.

Validity

There is no time limit.

When using this document the upto-dateness of above basis and the conformity of the product have to be observed.

Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.



Thomas Stefan, Dipl.-Ing. (FH) Head of Testing Department Building Component Testing

Dimitrios Moustakidis, MSc, Dipl.-Ing. Operating Testing Officer Building Component Testing

Identity-Check



www.ift-rosenheim.de/ift-geprueft ID: 5D8-BDC05

ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 D-83026 Rosenheim Contact Phone: +49 8031 261-0 Fax: +49 8031 261-290 www.ift-rosenheim.de Testing and Calibration – EN ISO/IEC 17025 Inspection – EN ISO/IEC 17020 Product Certification – EN ISO/IEC 17065 Certification of Management Systems – EN ISO/IEC 17021





Class: C1/B1

Class: 3

Watertightness according to EN 12208:1999-11

Air permeability according to EN 12207:2016-12

Resistance to wind load according to EN 12210:2016-03



Number

Owner

Product

Details

Result

Designation

Special features

Class: 3A

ift Rosenheim 21.04.2020