ift-Nachweis



Classification Report

Number 21-001708-PR01 (NW-A01-0203-en-01)

Owner Europa Profil Aluminio S.A.

56th Klm National Highway Athens - Lamia 32011 Innofita Viotas

Greece

Product Single sash lifting-sliding door

Designation System: EUROPA ESS34

Shipping name: ESS 34 SINGLE L&S POCKET DOOR

Details Manufacturer Europa Profil Aluminio S.A., - Innofita Viotas;

Material Aluminium system with thermal break; Type of opening Lifting sliding; Opening direction To the right (seen from inside);

Overall dimensions (W x H) 1600 mm x 2200 mm

Special features Test sequence. Material compatibility must be taken into

account. Material durability must be taken into account. The strength, durability and material compatibility of the adhesive system was not part of the test and is tested sep-

arately.

Result

Operating forces according to EN 13115:2001-07



Class: 1

Air permeability according to EN 12207:2016-12



Class: 4

Resistance to wind load according to EN 12210:2016-03



Class: C3/B3

Watertightness according to EN 12208:1999-11



Class: 9A

ift Rosenheim 08.04.2021

Robert Kolacny, Dipl.-Ing. (FH)
Deputy Head of Testing Department
Building Component Testing

Dimitrios Moustakidis, MSc, Dipl.-Ing. Operating Testing Officer Building Component Testing

Basis *)

EN 14351-1:2006+A2:2016-09
*) and corresponding national versions
(e.g. DIN EN)

Test report: 21-001708-PR01 PB-A01-0203-en-01

Representation



Instructions for use

The Evidence ("Nachweis") can be used for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The results obtained apply to the direct field of application determined in Annex E of EN 14351-1.

Validity

There is no time limit.

When using this document the upto-dateness of above basis and the conformity of the product have to be observed.

Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

Identity-Check



www.ift-rosenheim.de/ift-geprueft ID: B1A-BFE9D





